

UPS 8S Power RT series

1KVA ~ 3KVA
PF 0.9



Features

- High frequency on-line double conversion technology
- DSP (Digital signal processors) control technology
- Active power factor correction (APFC), input power factor up to 0.99
- Output power factor 0.9
- Wide input voltage range (110V ~ 300Vac) and frequency range (40 ~ 70Hz)
- Auto sensing frequency
- 50/60Hz frequency conversion
- Cold start
- Rear ventilation design and variable speed fan
- Effective software and hardware protection
- Quick and stable charging, 90% capacity restored in 3 h (standard model UPS)


- Linear derating in low voltage input reducing battery discharging times
- Settable delayed start when power is restored
- Advanced battery management (ABM)
- Multiple functions settable via LCD: output voltage, EOD, auto-start, bypass mode, ECO mode and frequency conversion mode
- Multi-platform communications: RS232 (standard), USB / RS485 / SNMP / dry contacts (optional)

Available Options

- Optional USB, RS485 card, AS400 dry contacts, SNMP card, SMS alarms, EPO function, MBS (External maintenance bypass switch)

Rear Panel

1. Overcurrent Protection
2. AC Input
3. Modem/Tel/Fax
4. DC Input
5. Outlet
6. FAN
7. RS232
8. EPO (optional)
9. USB (optional)
10. Intelligent Slot



Optional sockets

Specifications

MODEL	8S Power U1001RTS1	8S Power U1002RTS1	8S Power U1003RTS1				
Capacity	1 KVA / 900 W	2 KVA / 1800 W	3 KVA / 2700 W				
INPUT							
Rated voltage	208 V / 220 V / 230 V / 240 Vac						
Voltage range	110 ~ 176 Vac (linear derating between 50% and 100% load); 176 ~ 280 Vac (no derating); 280 ~ 300 Vac (derating 50%)						
Frequency	40 ~ 70 Hz (auto-sense)						
Power factor	≥ 0.99						
Bypass voltage range	-25% ~ +15% (settable)						
OUTPUT							
Voltage	208 V / 220 V / 230 V / 240 Vac (settable via LCD)						
Voltage regulation	± 1%						
Frequency	45 ~ 55 Hz or 55 ~ 65 Hz (synchronized range); 50 / 60 Hz ± 0.1 Hz (battery mode)						
Waveform	Sinusoidal						
Crest factor	3:1						
Harmonic distortion	≤ 2% (linear load); ≤ 5% (non-linear load)						
Transfer time	Mains mode to battery mode: 0 ms Inverter mode to bypass mode: 4 ms (typical)						
Overload capability	105% ~ 125%: transfer to bypass in 1 min; 125% ~ 150%: transfer to bypass in 30 s; > 150%: transfer to bypass in 300 ms						
EFFICIENCY							
Mains mode	≥ 90%	≥ 91%	≥ 92%				
Battery mode	≥ 85%	≥ 86%	≥ 87%				
ECO mode	≥ 95%	≥ 96%	≥ 97%				
BATTERIES							
DC voltage	24 V	36 V	36 V				
Inbuilt battery	2 × 9 Ah	3 × 7 Ah	/				
Charging current (max.)	1 A	6 A	1 A				
Recharge time			8 h				
ALARMS							
Utility failure		4 s per beep					
Low battery		1 s per beep					
Overload		1 s twice beep					
UPS fault		Long beep					
COMMUNICATIONS							
RS232 (standard) / USB (optional)	Supports Windows® 98 / 2000 / 2003 / XP / Vista / 2008 / Windows® 7 / 8 / 10						
SNMP (optional)	Power management from SNMP manager and web browser						
OTHERS							
Operating temperature	0 ~ 40°C						
Relative Humidity	0 ~ 90% (non-condensing)						
Dimensions (W × D × H) (mm)	440 × 468 × 88		440 × 658 × 88	440 × 468 × 88	440 × 658 × 88	440 × 468 × 88	440 × 468 × 88
Packaged dimensions (W × D × H) (mm)	545 × 592 × 198		545 × 782 × 198	545 × 592 × 198	545 × 782 × 198	545 × 592 × 198	545 × 592 × 198
Net weight (kg)	12.26	13.78	7.58	22.73	25.86	9.66	29.26
Gross weight (kg)	15.78	17.3	11.1	26.63	29.76	13.18	33.16

●Derate capacity to 70% in CUCF mode and to 90% when the output voltage is adjusted to 208Vac.

●S means standard model, H means long time model.

●All specifications subject to change without notice.

●Custom-made specifications are acceptable.