

Data sheet

6ES7332-5HF00-0AB0



Figure similar

SIMATIC S7-300, Analog output SM 332, isolated, 8 AO, U/I; diagnostics; resolution 11/12 bits, 40-pole, removing and inserting possible with active backplane bus

Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V
• Reverse polarity protection	Yes
Input current	
from load voltage L+ (without load), max.	340 mA
from backplane bus 5 V DC, max.	100 mA
Power loss	
Power loss, typ.	6 W
Analog outputs	
Number of analog outputs	8
Voltage output, short-circuit protection	Yes
Voltage output, short-circuit current, max.	25 mA
Current output, no-load voltage, max.	18 V
Output ranges, voltage	
• 0 to 10 V	Yes
• 1 V to 5 V	Yes
• -10 V to +10 V	Yes
Output ranges, current	
• 0 to 20 mA	Yes
• -20 mA to +20 mA	Yes
• 4 mA to 20 mA	Yes
Load impedance (in rated range of output)	
• with voltage outputs, min.	1 kΩ
• with voltage outputs, capacitive load, max.	1 μF
• with current outputs, max.	500 Ω
• with current outputs, inductive load, max.	10 mH
Cable length	
• shielded, max.	200 m
Analog value generation for the outputs	
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	12 bit; ±10 V, ±20 mA, 4 mA to 20 mA, 1 V to 5 V: 11 bit + sign; 0 V to 10 V, 0 mA to 20 mA: 12 bit
• Conversion time (per channel)	0.8 ms
Settling time	
• for resistive load	0.2 ms
• for capacitive load	3.3 ms
• for inductive load	0.5 ms; 0.5 ms (1 mH); 3.3 ms (10 mH)
Errors/accuracies	

Operational error limit in overall temperature range					
• Voltage, relative to output range, (+/-)	0.5 %				
• Current, relative to output range, (+/-)	0.6 %				
Basic error limit (operational limit at 25 °C)					
• Voltage, relative to output range, (+/-)	0.4 %				
• Current, relative to output range, (+/-)	0.5 %				
Interrupts/diagnostics/status information					
Diagnostics function	Yes; Parameterizable				
Alarms					
• Diagnostic alarm	Yes; Parameterizable				
Diagnoses					
• Diagnostic information readable	Yes				
Diagnostics indication LED					
• Group error SF (red)	Yes				
Potential separation					
Potential separation analog outputs					
• between the channels	No				
• between the channels and backplane bus	Yes				
• Between the channels and load voltage L+	Yes				
• between the channels and the power supply of the electronics	Yes				
Isolation					
Isolation tested with	500 V DC				
connection method					
required front connector	40-pin				
Dimensions					
Width	40 mm				
Height	125 mm				
Depth	117 mm				
Weights					
Weight, approx.	272 g				
Classifications					
	Version	Classification			
	eClass	14			
	eClass	12			
	eClass	9.1			
	eClass	9			
	eClass	8			
	eClass	7.1			
	eClass	6			
	ETIM	9			
	ETIM	8			
	ETIM	7			
	IDEA	4			
	UNSPSC	15			
		3562			
		EC001420			
		EC001420			
		EC001420			